

| | |
|---|---------------|
| Allgemeines | |
| Einführung, Elektrische Daten | 4.04 |
| Festinduktivitäten | |
| SM-0603 CG* | 4.05 |
| SM-0805* | 4.08 - 4.09 |
| SM-NE 29* | 4.10 |
| SM-1206 | 4.11 |
| SM-NE 30* | 4.12 |
| SM-NE 45* | 4.13 - 4.14 |
| SM-NE 56 | 4.15 - 4.16 |
| SM-NE 0718 | 4.17 |
| SM-NE 95 H* | 4.18 |
| SM-NE 127 | 4.19 |
| SM-NE 150 | 4.20 |
| RFID Transponderspulen / Induktivitäten | |
| Ms 2046 | 4.25 |
| Ms 18 k | 4.28 |
| Ms 2074 / L | 4.29 |
| Ms 32 c* / Ms 32 k / Ms 32 ka | 4.30 - 4.32 |
| Ms 34 | 4.33 |
| Ms 62 s / L | 4.34 |
| Ms 65 s / L | 4.35 |
| Z-Antenne SM-W 902 / SM-WA 903 | 4.38 |
| 2D77 Antenne | 4.39 |
| 3D Antenne 3D 11 25 / 3D 1130 | 4.40 |
| 3D Antenne 3D 15 / 3D 15a | 4.41 - 4.42 |
| Umspritzte Antenne | 4.43 |
| SMD-Mikrospule Ms 36 / L | 4.44 |
| Festinduktivität / Übertrager Ms 40 | 4.45 |
| Ms 42* / SMs 42* | 4.46 - 4.47 |
| Ms 50* / SMs 50* | 4.48 - 4.49 |
| Ms 75* | 4.50 |
| Ms 85* / SMs 85* | 4.51 - 4.52 |
| Ms 95* / Ms 95 a / SMs 95 / SMs 95 p* | 4.53 - 4.55 |
| Abgleichbare Luftspulen | |
| mit Saugfläche SM-L .. / ..* | 4.58 - 4.65 |
| mit Pick & Place Kappe SM-L 1,5* | 4.66 |
| Stabkerndrosseln für Stromversorgungen | |
| Produktinformation | 4.67 |
| Stabkerndrossel SM-Z1,5; SM-Z 4 L; SM-Z 6 L | 4.68 - 4.70 |
| Spule, abgleichbar SMF 5.1* | 4.71 - 4.73 |
| Übertrager Ms 35 | 4.74 |
| Breitbandübertrager / Richtkoppler | |
| Breitbandübertrager SM-T4 | 4.75 - 4.81 |
| Richtkoppler SM-T5 / SM-T5 a | 4.82 |
| Richtkoppler SM-T6 / SM-T7 | 4.83 - 4.86 |
| Zweifachverteiler | 4.87 - 4.89 |
| Specification Checklist Breitbandübertrager | 4.90 |
| Vierfachverteiler | 4.91 |
| Stromkompensierte CAN-Bus-Drosseln | |
| SM-R2,5 | 4.92 - 4.93 |
| SM-R4 | 4.94 - 4.96 |
| Ringkern-Übertrager SM-R6 | 4.97 |
| Stromkompensierte Ringdrossel SM-R10* | 4.98 |
| Hochspannungs-Trafo CCFL | 4.99 |
| Kundenspezifische Wandler & Übertrager | |
| Bauformen E, EP, RM und ER | 4.100 - 4.103 |
| Formblätter für Ihre Anfrage | 4.104 |
| Helix-Filter SM-H82; SM-H82H | 4.105 |
| Dämpfungperle SM-B5; SM-B9 | 4.107 |
| 2-fach EMI Bead | 4.108 |
| SMB-1,5 T / SMB-2,5 T | 4.109 |
| Verpackungsspezifikationen | 4.110 - 4.111 |
| Designer's Kits | 4.112 |

General Information

Introduction, Electrical data

Chip / Power inductors

SM-0603*
SM-0805*
SM-NE 29*
SM-1206
SM-NE 30*
SM-NE 45*
SM-NE 56
SM-NE 0718
SM-NE 95 H*
SM-NE 127
SM-NE 150

RFID Transponder coils / inductors

Ms 2046
Ms 18 k
Ms 2074 / L
Ms 32 c* / Ms 32 k / Ms 32 ka
Ms 34
Ms 62 s / L
Ms 65 s / L
Z-Antenna SM-W 902 / SM-WA 903
2D77 Antenna
3D Antenna 3D 11 25 / 3D 11 30
3D Antenna 3D 15 / 3D 15a
Covered antenna
SMD-Micro coil Ms 36 / L
Power inductor / transformer Ms 40
Ms 42* / SMs 42*
Ms 50* / SMs 50*
Ms 75*
Ms 85* / SMs 85*
Ms 95* / Ms 95 a / SMs 95 / SMs 95 p*

Tunable Air coil

with pick & place surface SM-L .. / ..*
with pick & place cap SM-L 1,5*

Rod core chokes for power supply

Product information
Rod core choke SM-Z1,5; SM-Z 4 L; SM-Z 6 L

Tuneable RF coil SMF 5.1*

Transformer Ms 35

Wideband transformer / Directional coupler

Wideband transformer SMT4
Directional coupler SM-T5 / SM-T5 a
Directional coupler SM-T6 / SM-T7
Two-way power combiner / divider
Specification Checklist Wideband transformer
Four-way power combiner / divider

Current-compensated CAN-Bus-chokes

SM-R2,5
SM-R4

Toroidal-core transformer SM-R6

Current-compensated toroidal-core choke SM-R10*

High voltage transformer CCFL

Converter & transformer to customer's specification

Types E, EP, RM and ER
Inquiry forms

Helical Filter SM-H82; SM-H82H

Bead inductor SM-B5; SM-B9

SMD Common mode choke for EMI-suppression

SMB-1,5 T / SMB-2,5 T

Tape and reel specifications

Designer's Kits